# **Product Data Sheet**

# DSM BRIGHT SCIENCE. BRIGHTER LIVING.

# NeoCryl® B-885

NeoCryl® B-885 is a solid methacrylic copolymer with easy solubility and good chemical resistance for use in a variety of coatings, lacquers and inks.

Product characteristics

Type - BMA/MMA copolymer

Average mol. weight - 50.000

# Film properties


- Excellent pigment grinding properties
- High gloss level
- Good adhesion to a variety of filmic substrates and metals
- Good plasticizer resistance

#### Recommendations on formulation and use

- Gravure and screen inks
- Clear and pigmented coatings on plastics and metals
- Car refinishing paints and aerosols

# Formulating guidelines

- NeoCryl® B-885 is soluble in esters, aromatics, ketones and chlorinated solvents
- Compatible with vinyls, other acrylics, chlorinated rubber, CAB and NC
- The low solution viscosity permits high application solids and pigment loading



**Product specifications** 

1 roddot spoomodtions				
Property	Range	Unit	GAP	
	White free flowing			
Appearance	bead		0059	
Total volatile	Max 0.7	%	0025	
Visc. Brookfield 25°C				
40% in toluene	350-500	mPas	0020	

Other product data

Property	Value	Unit	GAP
Density	1.15	Kg/I	0006
Free monomer	Max 0.7	%	0025
Tg (DSC)	85	°C	1140
Acid value	5	mg KOH/g	0095

### Test methods

Test methods (GAP) referred to in the table are available on request.

### Storage guidelines

The resin should be stored indoors in an original, unopened and undamaged container in a dry place at storage temperature between 5 and 40°C. Exposure to direct sunlight should be avoided.

## Shelf life

Under above mentioned storage conditions, the shelf life of the resin will be 24 months ex work.

## Material safety

A material safety data sheet for this product is available on request.

The user is held to check the quality, safety and other properties of the product referred to herein. The information and recommendations in this document are to the best of our knowledge, reliable. However, no rights whatsoever can be derived from this document or the information contained therein by any party, other than those expressly accepted by a selling entity of the Royal DSM group of companies ("DSM Selling Entity") in a binding sale and purchase agreement for product referred to herein. For the avoidance of doubt THE ROYAL DSM GROUP OF COMPANIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR PURPOSE. Unless explicitly agreed to otherwise in writing by the DSM Selling Entity, all offers, quotations, sales and deliveries of DSM products are subject to the General Conditions of Sale of such DSM Selling Entity.

